

SONOleed features

- High performance acoustic membrane designed to attenuate impact noise
- Stable dimensions
- Unique design and density
- Light and easy to install
- Antimicrobial
- Water-repellent
- Made in Canada

LEED Information

Materials and Resources;

MR 3, MR 4, MR 5, MR 6.

Indoor Environmental Quality;

IEQ 1, IEQ 2.

Innovation & Design Process;

IDP 1.

Scope: CERAMIC AND GLUED WOOD FLOORS

Properties	Requirements	Nominal Value
Drive in 100 % strain or less	ASTM D-5034-95	5502 kPa 798 PSI
Robinson test	ASTM C-627 Cycle 1 - 14	Passed cycles 1 - 14 Approved: Light residential to Extra heavy commercial
Acoustic value	ASTM E-1007-04 ASTM E-989-06	FIIC 57 to 68
Thermal resistance	ASTM C-518	R = 0.27 RSI = 0.05

Physical Properties	Metric	Imperial
Density:	137.6 kg / m ³	8.59 lb / ft ³
Roll size:	1.47 m x 15.24 m	58 in x 50 ft
Area covered / roll:	22.45 m ²	241.6 ft ²
Thickness:	2.72 mm	0.1070 in
Weight / roll:	8.3 kg	18.4 lb
Number of rolls / skid:	25 rolls	

Ecological Properties

0 % - COV (g. / l.) - Volatile organic compounds

100% recycled and recyclable wood fibre

For additional information :
Customer support : 1 (800) 561-4279
Website : www.mslfibre.com

infoplus@mslfibre.com

Developed and
manufactured in
Canada

